

## **Duplicating Material**

#### **ENGLISH**

#### **INSTRUCTION FOR USE**

#### General Information

SternTek® Duplicating Material is a pourable duplicating material based on a silicone, which is characterized by high dimensional accuracy and precise reproduction of detail. Its high elasticity and high tear resistance also guarantee easy removal of the model from SternTek® Duplicating Material. The excellent reproduction of detail and dimensional stability of duplicating moulds fabricated using SternTek® Duplicating Material ensure optimal duplicating activities are several ensures recorded. duplicating results, even after months or several pouring procedures

SternTek $^{\circ}$  Duplicating Material meets the requirements of ADA Spec. No. 20, ISO 4823:1992, Type 3

- Advantages
   Records finest details
   1:1 Mixing ratio

  - Extreme precision
     Does not stick to metal
     High tear resistance
  - Releasable by compressed air
     High elasticity

  - Molds can be stored dry

#### Indication

For fabricating stone and investment duplicate models

#### Recommended Use

- 1. Place the model in a standard duplicating flask. The model should not be soaked in water before duplication and should be at room temperature
- Shake the bottles of SternTek® Duplicating Material thoroughly before use. Mix the catalyst and base in a ratio of 1:1 for approximately 30 seconds and mix until the material has a uniform, homogeneous color. SternTek® Duplicating Material is particularly suitable for manual mixing, though a vacuum mixer is recommended for mixing to ensure a consistent quality of the duplicate moulds. Approximately 100 g to 200 g of duplicating cateriol. material is required per duplication, depending on the size of the model.
- 3. Pour the duplicating material in a thin stream and always onto the same area of the model within 4 minutes.
- The model can be removed from the mold after a setting time of 30
- 5. Allow the duplicating mold to sit for a further 30 min. before pouring with standard stone or investment material to ensure elastic recovery of any distortion that occurred when removing the model. Adhere to the respective manufacturer's instructions for use. If the duplicating molds are to be used several times, allow a minimum of 30 min. between each duplication procedure.

### **Please Note**

- SternTek® Duplicating Material must be thoroughly shaken before use.
- . The caps are color coded (catalyst white, base red) to prevent mixing them up and contaminating the contents of the bottle

#### Interactions

Do not use in conjunction with condensation cured silicone.

Avoid contact with organic solvents or fluids containing solvent, as they could cause expansion of the material, which may lead to inaccuracy. Do not store SternTek® Duplicating Material close to solvents or volatile monomers, as steam absorption may lead to expansion.

Do not use with latex gloves.

Side effects are not known to date. In singular cases, hypersensitivity to components of the material cannot be excluded.

### **Technical Data**

Regular Set Mixing Ratio 1:1 Mixing time 30 sec. Working time 4 min Setting time 30 min.

#### Composition

Vinylsiloxane, silicon dioxide, pigments, additive, platinum catalyst.

#### Storage

Store in a dry place at a normal room temperature (15-25° C / 59-77° F). Do not use after expiration date

# Packaging Regular Set

SternTek® Duplicating Material, Regular Set 2 bottles (catalyst and base) @ 1 liter each

SternTek® Duplicating Material, Regular Set 2 bottles (catalyst and base)

@ 5 liters each

REF 222012

REF 222011

#### Keep away from children. For dental use only!

**Caution:** Federal (USA) law prohibits this device to sale by or on the order of a dentist (or properly licensed practitioner).

Symbol	Used For	Symbol	Used For
2	Do not reuse	Ω	Used by YYYY-MM- DD or YYYY-MM
LOT	Batch code	<b>M</b>	Manufac- turer
STERILE R	Sterilized using irradia- tion	NON STERILE	Symbol for Non-Sterile
$ m R_{only}$	Symbol for "Use by Prescription only"	<u> </u>	Caution, consult ac- companying documents
CE	Symbol for "European Conformity"	REF	Catalog number
EC REP	Authorized representa- tive in the European Community		

Distributed by:



Sterngold Dental, LLC 23 Frank Mossberg Drive Attleboro, MA 02703

+1.800.243.9942 or +1.508.226.5660

Made in Germany

European Representative: indigodental GmbH Fahltskamp 5, 25421 Pinneberg, Germany Ph: +49 (0) 4101 86 86 8-312 Fax: +49 (0) 4101 86 86 70 Email: european.rep@indigodental.com



EC REP